


# SPORTABLE SCOREBOARDS®

## SCOREBOARD SPECIFICATIONS

AT BAT <b>48</b>	BALL <b>3</b>	STRIKE <b>1</b>	OUT <b>2</b>	INNING <b>7</b>
GUEST <b>7</b>	RUNS <b>10</b>	HITS <b>18</b>	ERR <b>0</b>	
HOME <b>10</b>	<b>10</b>	<b>28</b>	<b>2</b>	



## MODEL 3393LED

Please specify scoreboard color:



ROYAL GREEN PURPLE RED MAROON BLACK NAVY

### SPORTABLE SCOREBOARDS

106 MAX HURT DRIVE  
MURRAY, KY 42071

PHONE: 800-323-7745 • FAX: 270-759-4112  
www.sportablescoreboards.com

**PRODUCT OVERVIEW**

For elite baseball programs. Impressive 20' x 8' scoreboard features all of the game's essential information in a pro-format with huge 20" high super-bright 100,000-hour rated LED numerals with the widest viewing angle in the industry. SCORES, HITS and INNINGS go to 99. Customize your scoreboard - your team name or logo can be reproduced on this scoreboard. Scoreboard package includes: operator's keyboard, keyboard AC wall transformer, digit protective shields, junction box cover, mounting rails and complete operation, installation and service manual. 5-YEAR LIMITED WARRANTY.

**OVERALL DIMENSIONS**

8.0' height x 20.0' width x 8.0" depth

**WEIGHT**

Hanging weight: 1115 lbs.

Shipping weight: 1200 lbs.

**CONSTRUCTION**

18-gauge galvanized steel cabinet with powder coat finish for strength, durability, and lasting appearance

**POWER REQUIREMENTS****Scoreboard:**

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

**Controller:**

(1) 20-amp, 120-volt, 60-hertz, grounded AC circuit in a standard duplex outlet

**SCORING INFORMATION DISPLAYED**

**Home and Guest RUNS:** 2-digit displays, 0-99

**Home and Guest HITS:** 2-digit displays, 0-99

**Home and Guest ERRORS:** 1-digit display, 0-9

**AT BAT:** 2-digit displays, 0-99

**BALL:** 1-digit display, 0-9

**STRIKE:** 1-digit display, 0-9

**OUT:** 1-digit display, 0-9

**INNING:** 2-digit displays, 1-99

**DIGITS**

20.0" tall, 160° visibility, red, 100,000 hour-rated, outdoor, Super-Bright LED (displays Lexan Protective Digit Shields and Adjustable LED Intensity Included)

**CAPTIONS**

**HOME and GUEST:** 15.0" tall

**AT BAT, BALL, STRIKE, OUT, INNING, RUNS, HITS, and ERRORS:** 12.0" tall

**Polymeric Calendered Vinyl Lettering**

**APPROVALS****ETL/CSA listed**

**Scoreboard:** Meets all FCC Class A requirements

**2.4GHz wireless transmitter:** FCC Part 15 certified

**2.4GHz wireless receiver:** Meets all FCC Part 15 requirements

**WARRANTY**

This product is warranted against defects in materials and workmanship for a period of five (5) years from the date of invoice. This includes factory repair service for parts covered under warranty. Complete warranty details are included in the Instruction Manual shipped with each unit.

**SERVICING**

**Technical Support is available 24 hours a day, 7 days a week**

An access panel on the back of the scoreboard allows easy access to the electronic module, (the only working parts of the scoreboard), for ease of replacement/servicing. These universal, plug-in electronic modules are used in all of the manufacturer's scoreboards using Outdoor LED displays, and are 100% interchangeable between any of the manufacturer's Outdoor, permanent LED scoreboards.

**INSTALLATION**

This model may be installed between (2) 8" OD steel, schedule 40 poles; or (3) 8" I-beams, minimum. Hole, depth and diameter, as well as, pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.

***Support structure and mounting hardware supplied by customer***

**SCOREBOARD CONTROLLER**

**Dimensions:** 3.5" height x 15.5" width x 7.5" depth. **Weight:** 2 lbs.

The universal keyboard controller included with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad, and is capable of operating any of the manufacturer's scoreboard models. Large backlit LCD display; custom software; and game-specific keypad inserts minimize required input and ensures ease of operation. Fail-safe memory stores all scoring information and option settings for over five years. Options include 2.4GHz wireless control and external battery pack with automatic battery charger.

**Cable-Controlled System (standard) Includes:**

- (1) Universal LCD keyboard controller
- (3) BASEBALL keypad inserts
- (1) 12-volt DC wall transformer
- (1) Junction box cover with Receptacle (to be installed at scorekeeper's location)
- (1) 20-ft. Signal Cable (used to connect the keyboard to the junction box receptacle)
- (1) Project-specific length of 4 wire twisted pair, shielded control cable

**2.4GHz Wireless System (optional) Includes:**

- (1) Universal LCD keyboard controller (external battery pack with charger optional)
- (3) BASEBALL keypad inserts
- (1) 12-volt DC wall transformer
- (1) 2.4GHz transmitter (connects to keyboard controller via supplied interface cable)
- (1) 2.4GHz receiver (connects to the scoreboard, eliminating control cable and junction box installation)

**OPTIONS**

See Sportable Scoreboards catalog #67 for full list of options